

Product Page Heading

Features

- **High Quality Air:** Proven high-performance desiccant technology delivers -40°C (-40°F) pressure dew point air for critical applications; pre-filter and after-filter protect desiccant and downstream air from oil contamination and particulates
- **Easy to Maintain:** A low profile design and easy access to components simplifies installation and maintenance
- **Reliable Operation:** High-strength desiccant along with durable valves and components provide extended life
- **Reduced Energy Use:** Low pressure drop design saves on energy costs and provides an economical drying solution
- **Smart Control:** Easy to use, advanced microprocessor helps to maintain dryer performance at optimum levels, while constantly monitoring functions and provides maintenance alerts as well as protection notifications



Model Specifications

Model	Capacity m ³ /min (scfm)	Heater kW	Length x Width x Height mm (in)	Weight kg (lb)	Connection Air In/Out
EH150	4.2 (150)	2	813 (32.0) x 1,130 (44.5) x 1,676 (66.0)	344 (758)	1" NPT
EH200	5.7 (200)	3	813 (32.0) x 1,232 (48.5) x 1,702 (67.0)	414 (913)	1 1/2" NPT
EH250	7.1 (250)	3	889 (35.0) x 1,334 (52.5) x 1,727 (68.0)	508 (1,119)	1 1/2" NPT
EH300	8.5 (300)	3	889 (35.0) x 1,334 (52.5) x 1,727 (68.0)	540 (1,191)	1 1/2" NPT
EH400	11.3 (400)	4.5	864 (34.0) x 1,435 (56.5) x 2,083 (82.0)	698 (1,539)	2" NPT
EH500	14.2 (500)	4.5	864 (34.0) x 1,435 (56.5) x 2,083 (82.0)	774 (1,707)	2" NPT
EH600	17.0 (600)	6	1,194 (47.0) x 1,626 (64.0) x 2,184 (86.0)	1,075 (2,369)	3" NPT
EH800	22.7 (800)	9	1,194 (47.0) x 1,626 (64.0) x 2,184 (86.0)	1,216 (2,681)	3" NPT
EH1000	28.3 (1,000)	9	1,219 (48.0) x 1,994 (78.5) x 2,032 (80.0)	1,380 (3,043)	3" NPT
EH1200	34.0 (1,200)	12	1,219 (48.0) x 1,994 (78.5) x 2,032 (80.0)	1,490 (3,285)	3" NPT
EH1500	42.5 (1,500)	15	1,397 (55.0) x 2,134 (84.0) x 2,337 (92.0)	2,032 (4,480)	3" NPT
EH1800	51.0 (1,800)	18	1,524 (60.0) x 2,134 (84.0) x 2,337 (92.0)	2,248 (4,956)	4 FLG
EH2100	59.5 (2,100)	18	1,524 (60.0) x 2,134 (84.0) x 2,337 (92.0)	2,427 (5,350)	4 FLG
EH3000	84.9 (3,000)	30	1,854 (73.0) x 2,438 (96.0) x 2,540 (100.0)	3,515 (7,750)	4 FLG
EH4000	113.3 (4,000)	36	2,134 (84.0) x 2,591 (102.0) x 2,337 (92.0)	4,965 (10,950)	6 FLG
EH5000	141.6 (5,000)	50	2,311 (91.0) x 3,048 (120.0) x 2,464 (97.0)	6,009 (13,248)	6 FLG
H6000	169.9 (6,000)	60	2,413 (95.0) x 3,353 (132.0) x 2,616 (103.0)	7,120 (15,696)	6 FLG
EH8000	226.5 (8,000)	75	2,565 (101.0) x 3,962 (156.0) x 2,667 (105.0)	8,122 (17,910)	8 FLG



About Ingersoll Rand Inc. Ingersoll Rand Inc. (NYSE:IR), driven by an entrepreneurial spirit and ownership mindset, is dedicated to helping make life better for our employees, customers and communities. Customers lean on us for our technology-driven excellence in mission-critical flow creation and industrial solutions across 40+ respected brands where our products and services excel in the most complex and harsh conditions. Our employees develop customers for life through their daily commitment to expertise, productivity and efficiency. For more information, visit www.IRCO.com.