



## HLA Heatless Desiccant Dryers 2.5- 141.6 m<sup>3</sup>/min, 90-5,000 cfm

HLA heatless desiccant air dryers are designed to increase reliability and efficiency for consistent delivery of clean, dry compressed air. Our reliable, high strength, non-acidic desiccant provides maximum performance and is environmentally friendly.

### Features

- **Save on Space:** Low profile design allows dryer to be placed in areas with low overhead clearances
- **Easy, Safe Maintenance and Service:** Rear-mounted inlet and outlet manifolds provide convenient access to important valves and components
- **Rugged Design:** Standard NEMA 4 electrical panel for moisture-prone or hose-down industrial applications
- **Smart Control:** Enhanced controller provides precise pneumatic valve sequencing, automatic maintenance reminders and an easy to read status panel under all lighting conditions
- **Reliable Operation:** Long-life stainless steel switching and purge valves feature ceramic seats and an extended service interval



HLA 1800

## Model Specifications

Model	Capacity (-40°C (-40°F) Dew Point) nm <sup>3</sup> /min / scfm	In/Out Connection	Width mm/in	Depth mm/in	Height mm/in	Weight kg/lb
HLA90	2.5 / 90	1" NPT	1,029 / 40.5	762 / 30.0	1,603 / 63.1	215 / /475
HLA120	3.4 / 120	1" NPT	1,029 / 40.5	762 / 30.0	1,603 / 63.1	255 / 563
HLA160	4.5 / 160	1 1/2" NPT	1,130 / 44.5	813 / 32.0	1,679 / 66.1	321 / 563
HLA200	5.7 / 200	1 1/2" NPT	1,130 / 44.5	813 / 32.0	1,679 / 66.1	332 / 731
HLA250	71. / 250	1 1/2" NPT	1,232 / 48.5	813 / 32.0	1,697 / 66.8	394 / 869
HLA300	8.5 / 300	2" NPT	1,232 / 48.5	854 / 33.6	1,697 / 66.8	419 / 924
HLA400	11.3 / 400	2" NPT	1,334 / 52.5	910 / 35.8	1,722 / 67.8	506 / 1,115
HLA500	14.2 / 500	2" NPT	1,435 / 56.5	982 / 38.6	2,096 / 82.5	709 / 1,564
HLA600	17.0 / 600	2" NPT	1,435 / 56.5	982 / 38.6	2,096 / 82.5	755 / 1,664
HLA800	22.7 / 800	3" NPT	1,626 / 64.0	1,303 / 51.3	2,225 / 87.6	915 / 2,017
HLA1000	28.3 / 1,000	3" NPT	1,626 / 64.0	1,303 / 51.3	2,225 / 87.6	1,015 / 2,237
HLA1200	34.0 / 1,200	3" NPT	1,626 / 64.0	1,303 / 51.3	2,225 / 87.6	1,099 / 2,424
HLA1500	42.5 / 1,500	4" FLG	1,981 / 78.0	1,552 / 61.6	2,032 / 80.0	1,376 /3,034
HLA1800	51.0 / 1,800	4" FLG	2,134 / 84.0	1,539 / 60.6	2,334 / 91.9	1,771 / 3,905
HLA2100	59.5 / 2,100	4" FLG	2,134 / 84.0	1,539 / 60.6	2,334 / 91.9	1,941 / 4,279
HLA2700	76.5 / 2,700	4" FLG	2,134 / 84.0	1,544 / 60.8	2,334 / 91.9	2,234 / 4,926
HLA3300	93.5 / 3,300	6" FLG	2,438 / 96.0	1,676 / 66.0	2,540 / 100.0	1,338 / 2,950
HLA4000	113.3 / 4,000	6" FLG	2,438 / 96.0	1,676 / 66.0	2,540 / 100.0	1,360 / 3,000
HLA5000	141.6 / 5,000	6" FLG	2,591 / 102.0	1,829 / 72.0	2,337 / 92.0	1,792 / 3,950



About Ingersoll Rand Inc. Ingersoll Rand Inc. (NYSE:IR), driven by an entrepreneurial spirit and ownership mindset, is dedicated to helping make life better for our employees, customers and communities. Customers lean on us for our technology-driven excellence in mission-critical flow creation and industrial solutions across 40+ respected brands where our products and services excel in the most complex and harsh conditions. Our employees develop customers for life through their daily commitment to expertise, productivity and efficiency. For more information, visit [www.IRCO.com](http://www.IRCO.com).