



ECO-FILTER Intake Filtration System

The ECO-FILTER™ intake filtration system utilizes high-quality primary and secondary filter elements to provide reduced energy costs and longer on-stream life over substitutes. The intake assembly is available in both 24" x 24" and 18" x 18" configurations. The secondary element has a 40% lower clean pressure drop than substitute products and an 89% higher dust holding capacity.

Features

- Primary element has a removal efficiency of 99% @ 10um, and can be washed clean of dirt for reuse during maintenance intervals
- Secondary element has a 40% lower clean pressure drop than substitute products and an 90% higher dust holding capacity
- The intake assembly is available in both 24" x 24" and 18" x 18" configurations.



Model Specifications

Part Number	Size	Weight	Clean Pressure Drop	Dust Holding Capacity	Temperature Rating
AAP1400009-00871	18" x 18"	20 lb	0.64" wg @ 1500 cfm; 0.36" wg @ 1000 cfm	483 g @ 1500 cfm; 774 g @ 1000 cfm	200 F
AAP0540009-00873	24" x 24"	28 lb	0.76" wg @ 3000 cfm; 0.42" wg @ 2000 cfm	900 g @ 3000 cfm; 1200 g @ 2000 cfm	200F

Parts & Accessories



Centrifugal Oil Filters



ECO-SPIN Inertial Spin Filter



About Ingersoll Rand Inc. Ingersoll Rand Inc. (NYSE:IR), driven by an entrepreneurial spirit and ownership mindset, is dedicated to helping make life better for our employees, customers and communities. Customers lean on us for our technology-driven excellence in mission-critical flow creation and industrial solutions across 40+ respected brands where our products and services excel in the most complex and harsh conditions. Our employees develop customers for life through their daily commitment to expertise, productivity and efficiency. For more information, visit www.IRCO.com.