



Liquidator Zero-Loss Condensate Removal

The Liquidator™ is a pneumatically-powered zero-loss condensate removal solution. It uses a ball-float sensor to determine when the drain reservoir is full and open the drain valve. The Liquidator maintains a minimum liquid level within the reservoir to ensure that only condensate is removed from the system and that no process air escapes through the drain orifice.

Features

- As condensate enters accumulation reservoir, air returns to the system.
- Ball float rises as condensate accumulates in the reservoir.
- Float tether cable tenses as float rises.
- Linkage arm is pulled laterally by the tether cable
- Pilot air line is opened and pressurizes the piston cylinder.
- Pilot air compresses a pneumatic piston to open the discharge valve and drain condensate from the reservoir.
- Pilot air line closes and pneumatic piston retracts as float sinks.



Model Specifications

Attribute	Metric	Imperial
Weight	5 kg	11 lb
Reservoir Volume	1.54 L	52 oz
Volumetric Flow Rate	49.2 L/min	13.6 gal/min
Cycle Discharge Volume	1.3 L @ 7 barg	44 oz @ 100 psig
Fluid Port Size	15 mm	5/8 in.
Ball Valve Port Size	13 mm	1/2 in.
Allowable Fluid Temperature	1 to 65 C	34 to 150 F
Required Pilot Air Pressure	3.8 to 8.3 barg	55 to 120 psig
Max. Reservoir Pressure	17 barg	250 psig

Parts & Accessories



**MSG® TURBO-AIR®
Centrifugal Compressor**



**ReliaDrain Zero-Loss
Condensate Removal**



About Ingersoll Rand Inc. Ingersoll Rand Inc. (NYSE:IR), driven by an entrepreneurial spirit and ownership mindset, is dedicated to helping make life better for our employees, customers and communities. Customers lean on us for our technology-driven excellence in mission-critical flow creation and industrial solutions across 40+ respected brands where our products and services excel in the most complex and harsh conditions. Our employees develop customers for life through their daily commitment to expertise, productivity and efficiency. For more information, visit www.IRCO.com.