

## DRYER DATA SHEET

### Refrigerant Dryers

MODEL DATA				
1	Manufacturer	Ingersoll Rand		
2	Date	12/4/20		
3	Model Number	<b>DA340INA100</b>		
4	Cycling/Non-Cycling	<b>Non-Cycling</b>		
5	Refrigerant Type	<b>R134A</b>		
6	Air/Water Cooled	<b>Air</b>		
7	Voltage	<b>120</b>		
	<b>DESCRIPTION</b>	<b>FULL FLOW</b>	<b>10% FLOW</b>	<b>UNITS</b>
8	Tested Flow	<b>200</b>	<b>20</b>	scfm <sup>b</sup>
9	Outlet Pressure Dewpoint	<b>50</b>	<b>47</b>	°F
10	Pressure Drop	<b>2.20</b>	<b>.20</b>	psi(d)
11	Total Dryer Input Power	<b>1.209</b>	<b>1.088</b>	kW
12	Specific Package Power <sup>c</sup>	<b>.61</b>	<b>5.44</b>	kW/100 scfm

Notes:

- a. Dryer ratings at the following inlet conditions to the dryer (as per ISO 7183, Table 2, Option A2):
  - Inlet Compressed Air Temperature: 100°F (38°C)
  - Inlet Compressed Air Pressure: 100 psig (7 Bar)
  - Max. Ambient Air Temperature: 100°F (38°C)
  - Inlet Compressed Air Relative Humidity: 100% (Saturated)
- b. SCFM defined as the volume of free air in cubic feet per minute measured at 14.5 psia (1.0 Bar), 68°F (20°C) temperature and 0% R.H. (0 WVP).
- c.  $(\text{Total Dryer Input Power}/\text{tested flow}) \times 100$

Member                      This form was developed by the Compressed Air and Gas Institute for the use of its members. CAGI has not independently verified the reported data.



Consult the CAGI website, [www.cagi.org](http://www.cagi.org), for a list of participants in the third party verification program.