



Ultra EL Lubricant

Ingersoll Rand Ultra Extended Life (EL) advanced synthetic lubricant performs up to twice as long as other rotary lubricants, keeping your compressors running at peak performance, minimizing downtime and lowering lifecycle costs.

Features

- **Up to 16,000 hours of lubricant run time** -- twice as long as other synthetic rotary lubricants -- maximizes uptime for critical equipment
- **Advanced cooling**, delivered by an ultra-high thermal conductivity value, enables compressors to run cooler and more efficiently, even in high-ambient temperature environments
- **Peak compressor performance** significantly reduces wear, delivering the highest efficiency, while dramatically increasing component longevity
- **More reliable lubricant performance** provides more consistent productivity in your operation
- **High flash point** of 272 °C (522 °F), higher than most poly-alpha-olefins (PAOs), diesters and other synthetic lubricants, enhances operational safety
- **Significantly improved separation qualities** r Significantly improved separation qualities so more lubricant stays in your compressor

AFTER 8,000 HOURS...





Using Ultra EL Lubricant



NOT using Ultra EL Lubricant

Model Specifications

Bottle Size	OEM Part #
1 Liter (0.3 gallons)	Part # 24161119
5 liters (1.2 gallon)	Part # 24061608
15 liters (4.0 gallons)	Part # 24061624
208 liters (55 gallons)	Part # 24061640



Ingersoll Rand (NYSE:IR) advances the quality of life by creating comfortable, sustainable and efficient environments. Our people and our family of brands—including Club Car®, Ingersoll Rand®, Thermo King® and Trane®—work together to enhance the quality and comfort of air in homes and buildings; transport and protect food and perishables; and increase industrial productivity and efficiency. We are a \$14 billion global business committed to a world of sustainable progress and enduring results. For more information, visit www.ingersollrand.com.