

Ingersoll Rand (EDV) , , , , . EDV , , / .

Features

EDV . , , , . EDV y .

S

, . LED .

- NEMA 4 (IP65) -
- CE & UL-
- SBV -
- -
- / -
- / -
- -



EDV Specifications			
Feature	Data	Feature	Data
Timer Interval	0.5-45 minutes	Manual Override	Yes
Drain Cycle	0.5-10 seconds	Seals	Viton®
Maximum Air Pressure	250 psig (17.25 bar)	LEDs	Ultrabright
Dimensions	4.75" x 3.5" x 2" (121 mm x 89 mm x 51 mm)	Controls	Large, easy to read and adjust
Weight	1.5 lb (680 g)	Mounting	NPT or BSP connections
Operating Temperature		Enclosure NEMA 4 (IP)	Yes
Fluid	33°F-265°F (1°C - 129°C)	Valve Plunger	18FM
Ambient	4°F-125°F (-16°C - 52°C)	Valve Body	Low lead brass (≤ 0.5%)

Model Specifications

ModelName	Inlet Connection (mm / in)	Orifice Diameter (mm / in)	Outlet Connection (mm / in)	Voltage
3.7995891E7	12.7 / 0.5 NPT	10.7 / 7/16	12.7 / 0.5 NPT	110/120V
3.7995909E7	6.4 / 0.25 NPT	10.7 / 7/16	6.4 / 0.25 NPT	230/240V
3.7995917E7	12.7 / 0.5 NPT	10.7 / 7/16	12.7 / 0.5 NPT	230/240V
3.7995925E7	6.4 / 0.25 NPT	2.3 / 3/32	6.4 / 0.25 NPT	110/120V
3.7995933E7	6.4 / 0.25 NPT	2.3 / 3/32	6.4 / 0.25 NPT	230/240V
5.4410931E7	6.4 / 0.25 NPT	10.7 / 7/16	6.4 / 0.25 NPT	110/120V
5.4579248E7	JIC-14	2.3 / 3/32	6.4 / 0.25 NPT	110/120V
9.7339402E7	JIC-14	2.3 / 3/32	6.4 / 0.25 NPT	230/240V



Ingersoll Rand (NYSE:IR) advances the quality of life by creating comfortable, sustainable and efficient environments. Our people and our family of brands—including Club Car®, Ingersoll Rand®, Thermo King® and Trane®—work together to enhance the quality and comfort of air in homes and buildings; transport and protect food and perishables; and increase industrial productivity and efficiency. We are a \$14 billion global business committed to a world of sustainable progress and enduring results. For more information, visit www.ingersollrand.com.