



# Material Safety Data Sheet

INGERSOLL RAND

**Product name:** Ingersoll Rand Ultra Coolant

**Issue Date:** 2018.05.1

**Print Date:** 2018.05.1

INGERSOLL RAND encourages and expects you to read and understand the entire (M)SDS, as there is important information throughout the document. We expect you to follow the precautions identified in this document unless your use conditions would necessitate other appropriate methods or actions.

## 1. PRODUCT AND COMPANY IDENTIFICATION

**Product name:** Ingersoll Rand Ultra Coolant

### Recommended use of the chemical and restrictions on use

**Identified uses:** Selection of the appropriate polyglycol product for a specific application requires knowledge of the fluid requirements of the application, awareness of the most important of these requirements, and a match-up with the properties of the various polyglycol materials. Polyglycol products can be formulated for use in numerous industry applications such as hydraulic fluids, quenchants, compressor and refrigeration lubricants, heat transfer fluids, machinery lubricants, solder assist fluids, metalworking lubricants, textile finishing, etc.

### COMPANY IDENTIFICATION

DISTRIBUTED BY  
INGERSOLL RAND  
800D BEATY ST  
DAVIDSON, NC 28036  
UNITED STATES

**Customer Information Number:** +01 704-655-4000

### EMERGENCY TELEPHONE NUMBER

**U.S. 24-Hour Emergency #:** 800-424-9300

**Outside U.S. Emergency #:** +01 703-527-3887

## 2. COMPOSITION/INFORMATION ON INGREDIENTS

This product is a mixture.

CASRN / EC-No. / Index-No.	Concentration	Component	Classification
CASRN Confidential EC-No. Polymer Index-No. —	> 60.0 - < 70.0 %	Polypropylene glycol	Not classified

**Product name: Ingersoll Rand Ultra Coolant****Issue Date: 2018.05.1**

<b>CASRN</b> Confidential <b>EC-No.</b> Confidential <b>Index-No.</b> —	> 25.0 - < 30.0 %	Pentaerythritol ester	Not classified
<b>CASRN</b> 68411-46-1 <b>EC-No.</b> 2701281 <b>Index-No.</b> —	> 4.0 - < 6.0 %	Alkylated diphenylamine	R52/53

---

### 3. HAZARDS IDENTIFICATION

---

**Hazard classification**

Not classified as hazardous according to regulatory criteria.

**Other hazards**

no data available

---

### 4. FIRST AID MEASURES

---

**Description of first aid measures**

**General advice:** If potential for exposure exists refer to Section 8 for specific personal protective equipment.

**Inhalation:** Move person to fresh air; if effects occur, consult a physician.

**Skin contact:** Wash off with plenty of water.

**Eye contact:** Flush eyes thoroughly with water for several minutes. Remove contact lenses after the initial 1-2 minutes and continue flushing for several additional minutes. If effects occur, consult a physician, preferably an ophthalmologist.

**Ingestion:** No emergency medical treatment necessary.

**Most important symptoms and effects, both acute and delayed:** Aside from the information found under Description of first aid measures (above) and Indication of immediate medical attention and special treatment needed (below), any additional important symptoms and effects are described in Section 11: Toxicology Information.

**Indication of any immediate medical attention and special treatment needed**

**Notes to physician:** No specific antidote. Treatment of exposure should be directed at the control of symptoms and the clinical condition of the patient.

---

## 5. FIREFIGHTING MEASURES

---

**Suitable extinguishing media:** Water fog or fine spray. Dry chemical fire extinguishers. Carbon dioxide fire extinguishers. Foam. Alcohol resistant foams (ATC type) are preferred. General purpose synthetic foams (including AFFF) or protein foams may function, but will be less effective.

**Unsuitable extinguishing media:** Do not use direct water stream. May spread fire.

**Special hazards arising from the substance or mixture**

**Hazardous combustion products:** During a fire, smoke may contain the original material in addition to combustion products of varying composition which may be toxic and/or irritating. Combustion products may include and are not limited to: Nitrogen oxides. Carbon monoxide. Carbon dioxide.

**Unusual Fire and Explosion Hazards:** Container may rupture from gas generation in a fire situation. Violent steam generation or eruption may occur upon application of direct water stream to hot liquids.

**Advice for firefighters**

**Fire Fighting Procedures:** Keep people away. Isolate fire and deny unnecessary entry. Use water spray to cool fire exposed containers and fire affected zone until fire is out and danger of reignition has passed. Fight fire from protected location or safe distance. Consider the use of unmanned hose holders or monitor nozzles. Immediately withdraw all personnel from the area in case of rising sound from venting safety device or discoloration of the container. Do not use direct water stream. May spread fire. Move container from fire area if this is possible without hazard. Burning liquids may be moved by flushing with water to protect personnel and minimize property damage.

**Special protective equipment for firefighters:** Wear positive-pressure self-contained breathing apparatus (SCBA) and protective fire fighting clothing (includes fire fighting helmet, coat, trousers, boots, and gloves). Avoid contact with this material during fire fighting operations. If contact is likely, change to full chemical resistant fire fighting clothing with self-contained breathing apparatus. If this is not available, wear full chemical resistant clothing with self-contained breathing apparatus and fight fire from a remote location. If protective equipment is not available or not used, fight fire from a protected location or safe distance.

---

## 6. ACCIDENTAL RELEASE MEASURES

---

**Personal precautions, protective equipment and emergency procedures:** Use appropriate safety equipment. For additional information, refer to Section 8, Exposure Controls and Personal Protection. Refer to section 7, Handling, for additional precautionary measures.

**Environmental precautions:** Material will float on water. Prevent from entering into soil, ditches, sewers, waterways and/or groundwater. See Section 12, Ecological Information.

**Methods and materials for containment and cleaning up:** Contain spilled material if possible. Collect in suitable and properly labeled containers. See Section 13, Disposal Considerations, for additional information.

---

## 7. HANDLING AND STORAGE

---

**Precautions for safe handling:** No special precautions required. Do not use sodium nitrite or other nitrosating agents in formulations containing this product. Suspected cancer-causing nitrosamines

**Product name: Ingersoll Rand Ultra Coolant****Issue Date: 2018.05.1**

could be formed. Spills of these organic materials on hot fibrous insulations may lead to lowering of the autoignition temperatures possibly resulting in spontaneous combustion.

**Conditions for safe storage:** Store in the following material(s): 316 stainless steel. Carbon steel. Glass-lined container. Polypropylene. Polyethylene-lined container. Stainless steel. Teflon. This material may soften and lift certain paint and surface coatings. Use product promptly after opening. Store in original unopened container. Unopened containers of material stored beyond the recommended shelf life should be retested against the sales specifications before use. Additional storage and handling information on this product may be obtained by calling your sales or customer service contact.

**Storage stability**

**Shelf life: Use within**  
24 Month

---

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

---

**Control parameters**

Exposure limits are listed below, if they exist.

None established

**Exposure controls**

**Engineering controls:** Use local exhaust ventilation, or other engineering controls to maintain airborne levels below exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, general ventilation should be sufficient for most operations. Local exhaust ventilation may be necessary for some operations.

**Individual protection measures**

**Eye/face protection:** Use safety glasses (with side shields). Safety glasses (with side shields) should be consistent with EN 166 or equivalent.

**Skin protection**

**Hand protection:** Use gloves chemically resistant to this material when prolonged or frequently repeated contact could occur. Use chemical resistant gloves classified under Standard EN374: Protective gloves against chemicals and micro-organisms. Examples of preferred glove barrier materials include: Butyl rubber. Chlorinated polyethylene. Polyethylene. Ethyl vinyl alcohol laminate ("EVAL"). Examples of acceptable glove barrier materials include: Natural rubber ("latex"). Neoprene. Nitrile/butadiene rubber ("nitrile" or "NBR"). Polyvinyl alcohol ("PVA"). Polyvinyl chloride ("PVC" or "vinyl"). Viton. When prolonged or frequently repeated contact may occur, a glove with a protection class of 4 or higher (breakthrough time greater than 120 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 1 or higher (breakthrough time greater than 10 minutes according to EN 374) is recommended. Glove thickness alone is not a good indicator of the level of protection a glove provides against a chemical substance as this level of protection is also highly dependent on the specific composition of the material that the glove is fabricated from. The thickness of the glove must, depending on model and type of material, generally be more than 0.35 mm to offer sufficient protection for prolonged and frequent contact with the substance. As an exception to this general rule it is known that multilayer laminate gloves may offer prolonged protection at thicknesses less than 0.35 mm. Other glove materials with a thickness of less than 0.35 mm may offer sufficient protection when only brief contact is expected. NOTICE: The selection of a specific glove for a particular

application and duration of use in a workplace should also take into account all relevant workplace factors such as, but not limited to: Other chemicals which may be handled, physical requirements (cut/puncture protection, dexterity, thermal protection), potential body reactions to glove materials, as well as the instructions/specifications provided by the glove supplier.

**Other protection:** When prolonged or frequently repeated contact could occur, use protective clothing chemically resistant to this material. Selection of specific items such as faceshield, boots, apron, or full-body suit will depend on the task.

**Respiratory protection:** Under intended handling conditions, no respiratory protection should be needed.

---

## 9. PHYSICAL AND CHEMICAL PROPERTIES

---

### Appearance

Physical state	Liquid.
Color	Brown
Odor	Mild
Odor Threshold	No test data available
pH	8 - 10 <i>ASTM E70</i> (16% in water/methanol, 1:10)
Melting point/range	Not applicable to liquids
Freezing point	See Pour Point
Boiling point (760 mmHg)	> 200 °C <i>Calculated.</i>
Flash point	<b>closed cup</b> 210 °C <i>ASTM D 93</i>
Evaporation Rate (Butyl Acetate = 1)	No test data available
Flammability (solid, gas)	Not applicable to liquids
Lower explosion limit	No test data available
Upper explosion limit	No test data available
Vapor Pressure	< 0.01 mmHg at 20 °C <i>ASTM E1719</i>
Relative Vapor Density (air = 1)	No test data available
Relative Density (water = 1)	0.9901 at 25 °C / 25 °C <i>ASTM D891</i>
Water solubility	< 0.1 % at 20 °C <i>Measured</i>
Partition coefficient: n-octanol/water	no data available
Auto-ignition temperature	388 °C <i>ASTM E659</i>
Decomposition temperature	No test data available
Kinematic Viscosity	49.7 - 56.4 cSt at 37.8 °C <i>ASTM D 445</i>
Explosive properties	no data available
Oxidizing properties	no data available
Liquid Density	0.9872 g/cm <sup>3</sup> at 25 °C <i>ASTM D941</i>
Molecular weight	No test data available
pour point	-28.9 °C <i>ASTM D97</i>

NOTE: The physical data presented above are typical values and should not be construed as a specification.

---

## 10. STABILITY AND REACTIVITY

---

**Reactivity:** no data available

**Chemical stability:** Thermally stable at typical use temperatures.

**Possibility of hazardous reactions:** Polymerization will not occur.

**Conditions to avoid:** Exposure to elevated temperatures can cause product to decompose. Generation of gas during decomposition can cause pressure in closed systems.

**Incompatible materials:** Avoid contact with: Strong acids. Strong bases. Strong oxidizers.

**Hazardous decomposition products:** Decomposition products depend upon temperature, air supply and the presence of other materials. Decomposition products can include and are not limited to: Aldehydes. Alcohols. Ethers. Hydrocarbons. Ketones. Organic acids. Polymer fragments.

---

## 11. TOXICOLOGICAL INFORMATION

---

*Toxicological information on this product or its components appear in this section when such data is available.*

### Acute toxicity

#### Acute oral toxicity

Very low toxicity if swallowed. Harmful effects not anticipated from swallowing small amounts.

LD50, Rat, male, > 5,000 mg/kg

#### Acute dermal toxicity

Prolonged skin contact is unlikely to result in absorption of harmful amounts.

LD50, Rabbit, > 2,000 mg/kg No deaths occurred at this concentration.

#### Acute inhalation toxicity

At room temperature, exposure to vapor is minimal due to low volatility; single exposure is not likely to be hazardous. For respiratory irritation and narcotic effects: No relevant data found. As product: The LC50 has not been determined.

### Skin corrosion/irritation

Brief contact is essentially nonirritating to skin.

Repeated contact may cause severe skin irritation with local redness and discomfort.

### Serious eye damage/eye irritation

May cause slight temporary eye irritation.

Corneal injury is unlikely.

**Sensitization**

Did not cause allergic skin reactions when tested in guinea pigs.

For respiratory sensitization:  
No relevant data found.

**Specific Target Organ Systemic Toxicity (Single Exposure)**

Evaluation of available data suggests that this material is not an STOT-SE toxicant.

**Specific Target Organ Systemic Toxicity (Repeated Exposure)**

Based on available data, repeated exposures to small amounts are not anticipated to cause significant adverse effects.

**Carcinogenicity**

No specific, relevant data available for assessment.

**Teratogenicity**

No specific, relevant data available for assessment.

**Reproductive toxicity**

No specific, relevant data available for assessment.

**Mutagenicity**

No specific, relevant data available for assessment.

**Aspiration Hazard**

Based on physical properties, not likely to be an aspiration hazard.

**COMPONENTS INFLUENCING TOXICOLOGY:****Polypropylene glycol****Acute inhalation toxicity**

At room temperature, exposure to vapor is minimal due to low volatility; single exposure is not likely to be hazardous. For respiratory irritation and narcotic effects: No relevant data found.

As product: The LC50 has not been determined.

For similar material(s): Rat, 8 Hour, No deaths occurred following exposure to a saturated atmosphere.

**Alkylated diphenylamine****Acute inhalation toxicity**

As product: The LC50 has not been determined.

---

---

**12. ECOLOGICAL INFORMATION**

---

*Ecotoxicological information on this product or its components appear in this section when such data is available.*

**Ecotoxicity****Acute toxicity to fish**

**Product name: Ingersoll Rand Ultra Coolant****Issue Date: 2018.05.1**

Material is not classified as dangerous to aquatic organisms (LC50/EC50/IC50/LL50/EL50 greater than 100 mg/L in most sensitive species).

LL50, Oncorhynchus mykiss (rainbow trout), static test, 96 Hour, > 100 mg/l, OECD Test Guideline 203 or Equivalent

**Acute toxicity to aquatic invertebrates**

EL50, Daphnia magna (Water flea), static test, 48 Hour, > 100 mg/l, OECD Test Guideline 202 or Equivalent

**Persistence and degradability**

**Biodegradability:** Material is readily biodegradable. Passes OECD test(s) for ready biodegradability. Material is inherently biodegradable (reaches > 20% biodegradation in OECD test(s) for inherent biodegradability).

10-day Window: Pass

**Biodegradation:** 83 %

**Exposure time:** 29 d

**Method:** OECD Test Guideline 301A or Equivalent

10-day Window: Not applicable

**Biodegradation:** 81 %

**Exposure time:** 28 d

**Method:** OECD Test Guideline 302B or Equivalent

**Bioaccumulative potential**

**Bioaccumulation:** No data available for this product.

**Mobility in Soil**

No data available.

**Results of PBT and vPvB assessment**

This mixture has not been assessed for persistence, bioaccumulation and toxicity (PBT).

**Other adverse effects**

No specific, relevant data available for assessment.

---

---

**13. DISPOSAL CONSIDERATIONS**

---

**Disposal methods:** Any disposal practice must be in compliance with all local and national laws and regulations. Do not dump into any sewers, on the ground, or into any body of water.

---

---

**14. TRANSPORT INFORMATION**

---

**Classification for ROAD and Rail transport:**

Not regulated for transport

**Classification for SEA transport (IMO-IMDG):**

Not regulated for transport

**Transport in bulk**

Consult IMO regulations before transporting ocean bulk



**Product name: Ingersoll Rand Ultra Coolant****Issue Date: 2018.05.1**

---

**according to Annex I or II  
of MARPOL 73/78 and the  
IBC or IGC Code**

**Classification for AIR transport (IATA/ICAO):**

Not regulated for transport

This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. Additional transportation system information can be obtained through an authorized sales or customer service representative. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.

---

**15. REGULATORY INFORMATION**

---

**Label**

Classification and labeling have been performed according to regulations.

**Hazard symbol and Indication of danger**

Not classified as hazardous according to regulatory criteria.

Contains: Barium dinonyl-naphthalene sulfonate  
May produce an allergic reaction.

Safety data sheet available for professional user on request.

:

---

**16. OTHER INFORMATION**

---

**Full text of the R-phrases given in Section 2**

R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

**Revision**

Identification Number: 101199624 / A146 / Issue Date: 2018.05.1 / Version: 6.0

Most recent revision(s) are noted by the bold, double bars in left-hand margin throughout this document.

INGERSOLL RAND urges each customer or recipient of this (M)SDS to study it carefully and consult appropriate expertise, as necessary or appropriate, to become aware of and understand the data contained in this (M)SDS and any hazards associated with the product. The information herein is provided in good faith and believed to be accurate as of the effective date shown

**Product name: Ingersoll Rand Ultra Coolant****Issue Date: 2018.05.1**

---

above. However, no warranty, express or implied, is given. Regulatory requirements are subject to change and may differ between various locations. It is the buyer's/user's responsibility to ensure that his activities comply with all federal, state, provincial or local laws. The information presented here pertains only to the product as shipped. Since conditions for use of the product are not under the control of the manufacturer, it is the buyer's/user's duty to determine the conditions necessary for the safe use of this product. Due to the proliferation of sources for information such as manufacturer-specific (M)SDSs, we are not and cannot be responsible for (M)SDSs obtained from any source other than ourselves. If you have obtained an (M)SDS from another source or if you are not sure that the (M)SDS you have is current, please contact us for the most current version.