

Next Generation R-Series Oil-Flooded Rotary Screw Air Compressors

15-22kw (20-30 hp), 50 Hz ie and ne Premium Efficiency

Ingersoll Rand works to keep you ahead of your competition with Next Generation R-Series air compressors that lower total cost of ownership through industry leading energy efficiency, reliable components and best-in-class delivered capacity.



World-class performance

- **State-of-the-art airend** delivers up to 17.5% improved efficiency and 18% more airflow capacity
- **IE3 premium TEFC motor** and optional variable speed drive (VSD) decrease energy demands
- **V-Shield™ technology** provides a totally integrated, leak-free design, featuring PTFE stainless steel braided oil hoses and O-ring face seals
- **Components that provide reliable air for life**, including a free-floating cooling system, two-stage air filters and elastomeric O-rings
- **PartsCARE™ service program** ensures proper maintenance and longer product life, as well as extends your warranty



- **Enhanced serviceability** ensures increased uptime with two-stage filtration, easy maintenance and Ingersoll Rand extended life, premium grade coolant
- **Xe-70M controller** provides full control and connectivity with easy-to-read diagnostics, resulting in less down time and increased productivity for your compressed air system
- **Hinged-door service access with integrated handles** provides quick, easy access to all user-maintainable components
- **Optional Total Air System (TAS)** with integrated dryer and 3-in-1 heat exchanger provides clean, dry air in a single package that minimises installation costs, reduces footprint and improves ISO air quality



Standard features include:	Optional features include:
Premium performance airend	Total Air System (TAS) package with integrated air dryer
Energy saving, intuitive Xe-70M Series controller with remote access	Outdoor modification/rain protection
Air-cooled, free-floating cooling system	Low ambient temperature protection as low as -10°C (14°F) ²
V-Shield™ vibration isolation, PTFE hoses, leak-free connections	High ambient temperature protection up to 50°C (122°F) ²
Noise attenuation enclosure with hinged removable doors for easy service access	Ultra EL lubricant (extended 16,000-hour life)
Packaged pre-filtration	Ultra FG lubricant (food grade)
Long-life Ultra Coolant with 8,000-hour life	Power outage automatic restart option (PORO)
Long-life filtration and separation elements	Flow control inlet modulation
Star-Delta reduced voltage starter	Phase monitor protection
IE3 TEFC motor	Comprehensive service and coverage plans with extended warranty
NEMA®/IP55 enclosure, rated for 46°C (115°F) ambient operation ¹	

1. NEMA Type-4 for fixed speed (ie) models, NEMA Type-12 for VSD (ne) models



ie Standard 50 Hz Performance

Model	Max pressure barg	Nominal power kW	Capacity (FAD)* m ³ /min	Dimensions (L x W x H)** mm	Weight (Air-cooled)** kg
RS15ie	7.5	15	2.83	1300 x 850 x 1300	631
RS15ie	8.5	15	2.66		631
RS15ie	10.0	15	2.38		636
RS15ie	14.0	15	1.76		636
RS18ie	7.5	18.5	3.48		665
RS18ie	8.5	18.5	3.28		665
RS18ie	10.0	18.5	3.00		670
RS18ie	14.0	18.5	2.29		670
RS22ie	7.5	22	4.05		685
RS22ie	8.5	22	3.85		685
RS22ie	10.0	22	3.48		690
RS22ie	14.0	22	2.78		690

ne Standard 50 Hz Performance

Model	Max pressure barg	Nominal power kW	Capacity (FAD)* m ³ /min	Dimensions (L x W x H)** mm	Weight (Air-cooled)** kg
RS15ne	10.0	15	2.34	1300 x 850 x 1300	722
RS18ne	10.0	18.5	2.86		736
RS22ne	10.0	22	3.41		749

ie Total Air System (TAS) 50 Hz Performance

Model	Max pressure barg	Nominal power kW	Capacity (FAD)* m ³ /min	Dimensions (L x W x H)** mm	Weight (Air-cooled)** kg
RS15ie	7.0	15	2.83	1800 x 850 x 1300	793
RS15ie	8.0	15	2.66		793
RS15ie	9.5	15	2.38		798
RS15ie	13.5	15	1.76		798
RS18ie	7.0	18.5	3.48		838
RS18ie	8.0	18.5	3.28		838
RS18ie	9.5	18.5	3.00		843
RS18ie	13.5	18.5	2.29		843
RS22ie	7.0	22	4.05		860
RS22ie	8.0	22	3.85		860
RS22ie	9.5	22	3.48		865
RS22ie	13.5	22	2.78		865

ne Total Air System (TAS) 50 Hz Performance

Model	Max pressure barg	Nominal power kW	Capacity (FAD)* m ³ /min	Dimensions (L x W x H)** mm	Weight (Air-cooled)** kg
RS15ne	9.5	15	2.42	1800 x 850 x 1300	909
RS18ne	9.5	18.5	2.95		923
RS22ne	9.5	22	3.51		936

*FAD (Free Air Delivery) is full package performance including all losses, tested per ISO 1217:2009 Annex C

**Weights and dimensions are for base model only and do not include receiver tank



IngersollRandProducts.com

Ingersoll Rand (NYSE:IR) advances the quality of life by creating comfortable, sustainable and efficient environments. Our people and our family of brands—including Club Car®, Ingersoll Rand®, Thermo King® and Trane®—work together to enhance the quality and comfort of air in homes and buildings; transport and protect food and perishables; and increase industrial productivity and efficiency. We are a \$14 billion global business committed to a world of sustainable progress and enduring results. For more information, visit www.ingersollrand.com.



Ingersoll Rand, IR and the IR logo, V-Shield are trademarks of Ingersoll Rand, its subsidiaries and/or affiliates. All other trademarks are the property of their respective owners. Ingersoll Rand compressors are not designed, intended or approved for breathing air applications. Ingersoll Rand does not approve specialised equipment for breathing air applications and assumes no responsibility or liability for compressors used for breathing air service. Nothing contained on these pages is intended to extend any warranty or representation, expressed or implied, regarding the product described herein. Any such warranties or other terms and conditions of sale of products shall be in accordance with Ingersoll Rand's standard terms and conditions of sale for such products, which are available upon request. Product improvement is a continuing goal at Ingersoll Rand. Any designs, diagrams, pictures, photographs and specifications contained within this document are for representative purposes only and may include optional scope and/or functionality and are subject to change without notice or obligation.

We are committed to using environmentally conscious print practices

© 2019 Ingersoll Rand IRITS-0119-005 EUEN 0319