

Airscout[®] Flow Meters

Compressed Air Management Solutions

The Airscout[®] Flow Meter from Ingersoll Rand measures key performance indicators of compressed air usage to identify waste, system inefficiencies and cost saving opportunities.

Measure, Manage and Save

Compressed air is the most expensive utility. Surprisingly, its consumption is not usually measured like electricity, water or gas. An air system that is not measured cannot be managed. In an average unmanaged system, only 50% of the compressed air produced is actually used for production. The other 50% is lost as waste due to leaks, misuse and artificial demand.

Most facilities know how much air they are producing, but few know how much they are using or wasting. By measuring compressed air usage, these losses are easily tracked and managed to increase system efficiency and reduce costs. Airscout Flow Meters remove any guesswork by collecting accurate measurements throughout a facility.



Benefits of Airscout Flow Meters

- Identify efficiency improvements
- Monitor system performance
- Leak management
- Air consumption cost allocation

When You Measure, You Can Manage

The Airscout Flow Meter is a 3-in-1 tool that measures mass flow, temperature and pressure simultaneously. All of these parameters are critical to properly measure compressed air, establish baseline air flow and identify waste and energy use. With Airscout there are no assumptions—it provides real data that empowers managers to make money saving decisions.



Energy Efficiency

The ratio between air demand and kW input is a key performance indicator to accurately measure system efficiency. By measuring demand-side air use and combining the results with kW measurements, Airscout Flow Meters help managers quantify energy consumption improvements.



Leak Management


Airscout Flow Meters reveal leakages in real time so that they can be addressed immediately. In addition, by establishing a baseline for overall air consumption, managers can quantify results of any improvement.



Cost Allocation

By using Airscout Flow Meters, managers can check where, when and how much air is being used, then allocate costs appropriately. Placing flow meters along the distribution points off of the main header pipe is an effective way of monitoring the demand side of a compressed air system.

Precision Measurement Where You Need it



Airscout In-Line Flow Meters

Airscout In-Line Flow Meters are designed for more permanent applications in piping sizes 2" or less (0.5", 1" and 2"). All in-line meters include inlet and outlet tubing with NPT connectivity to existing piping systems.

Configuration Options

- In-Line module with display for point-of-use readout and data logging
- In-Line with no display, ideal for integration into a system controller, computer or Airscout Terminal*



In-Line with display



Airscout Probe Flow Meters

The Airscout Probe is the ultimate tool for temporary assessments or for permanent installations and is ideal for compressed air piping sizes 2" and up.

Configuration Options

- Probe with display module for point-of-use readout and data logging
- Probe with connector cap, ideal for integration with a system controller, computer or Airscout Terminal*

Airscout Terminal

The Airscout Terminal is a remote display option that provides local readout on locations where the Airscout is placed in high or unreachable locations.

Terminal Includes

- 5 m/16.4 ft communication cable
- Modbus to Ethernet converter
- Inputs for Airscout Probe or In-Line and up to 4 analog inputs
- Power cord





Probe with connector cap



Airscout Flow Meter Product Features

The Airscout Flow Meter combines an extremely large measurement range with integrated direction sensitivity. This patented feature enables you to measure in-loop networks, and systems with large air receivers. Previously, these situations were difficult to assess, but with Airscout, measurement is easy for any installation.

Premier Measurement Capabilities

- 3-in-1 tool measures flow, pressure and temperature
- Standard bi-directional flow
- Displays include 2 million-point data logger

Configurations for Any Installation

- Temporary assessments
- Permanent monitoring systems
- Pipe sizes 0.5" and larger
- Suited for rotary, centrifugal and reciprocating technologies

Variety of Display Options

- Powerful data analysis software
- Multiple display options
- Built-in LCD display available
- Modbus RTU, 4-20 mA and pulse
- Connectivity to X-Series system controls



Ingersoll Rand (NYSE:IR) advances the quality of life by creating comfortable, sustainable and efficient environments. Our people and our family of brands—including Club Car®, Ingersoll Rand®, Thermo King® and Trane®—work together to enhance the quality and comfort of air in homes and buildings; transport and protect food and perishables; and increase industrial productivity and efficiency. We are a \$13 billion global business committed to a world of sustainable progress and enduring results.



ingersollrandproducts.com

Ingersoll Rand, IR, the IR logo and Airscout are trademarks of Ingersoll Rand, its subsidiaries and/or affiliates. All other trademarks are the property of their respective owners. Ingersoll Rand compressors are not designed, intended or approved for breathing air applications. Ingersoll Rand does not approve specialized equipment for breathing air applications and assumes no responsibility or liability for compressors used for breathing air service. Ingersoll Rand assumes no responsibility or liability for compressors used in any application other than compressed air. Nothing contained on these pages is intended to extend any warranty or representation, expressed or implied, regarding the product described herein. Any such warranties or other terms and conditions of sale of products shall be in accordance with Ingersoll Rand's standard terms and conditions of sale for such products, which are available upon request. Product improvement is a continuing goal at Ingersoll Rand. Any designs, bictures, photographs and specifications contained within this document are for representative purposes only and may include optional scope and/or functionality and are subject to change without notice or obligation.