

Upgrade - Variable Inlet Guide Vanes for Centrifugal Compressors

Our advanced Inlet Guide Vanes(IGVs)help in reducing the work input and offering power savings of up to 9% to your compression system. IGVsadjust the inlet air flow trajectory to match the same rotational direction as the first stage impeller and diffuser blades. The adjusted airflow requires the compressor to perform less work to deliver the rated air flow and pressure when the ambient temperature is below design day conditions.

Features

ENHANCEDPERFORMANCE:

- Saveenergy when running at turndown points
- Additional energy savings opportunity when operating at colder than design day conditions
- · Obtain maximum compressor flow rate range
- Optimize year-round operating costs
- Return on investment is frequently less than a year

UNIVERSALDESIGN:

- Replacesthe conventional inlet butterfly valve
- Mounts directly to the inlet flange of the compressor
- Designed for use on all Cameron centrifugal compressors

EASYTO INSTALL:

Retrofit an existing centrifugal compressor
with an inlet guide vane and an actuator to
operate with the current control system. An
inlet guide vane assembly is designed to
mount right on the existing inlet flange of the
compressor, so it can be installed with only
minor piping modification.

FULLYADJUSTABLE/ANES:

 Rather than a single blade like a butterfly valve, an inlet guide vane uses multiple blades or vanes to control gas flow. Each vane is triangular in shape and aerodynamically



position. They; recompletely variable for part load operation and can fully close for efficient compressor unloading.

HOW IT WORKS:

• When throttling back the compressor, the inlet vanes impart a whirling motion to the gas flow in the same direction of rotation as the impeller. This motion reduces work input at the impeller, requiring less power to deliver target flow and pressure. The savings begins as soon as the inlet guide vane starts closing from the full open position. This could be from reduced demand or operating on days colder than the design point.

LOW TEMPERATURE SPROVIDE ENERGYS AVINGS OPPORTUNITY:

 Centrifugal compressors are designed to produce required process flow and pressure on the hottest day of the year at the installed location. Whenever the ambient temperature drops below the design point, the compressor can deliver more flow at the same design pressure. If this additional flow is not required, the compressor intake must be throttled back to maintain the capacity required. In this situation, an IGV can provide substantial power savings over an inlet butterfly valve.

<u>Article – Variable Inlet Guide VanesBoost Centrifugal</u> <u>Air Compressor Efficiency</u>



About Ingersoll Rand Inc. Ingersoll Rand Inc. (NYSE:IR)driven by an entrepreneurial spirit and ownership mindset, is dedicated to helping make life better for our employees, customers and communities. Customers lean on us for our technology-driven excellence in mission-critical flow creation and industrial solutions across 40+ respected brands where our products and services excel in the most complex and harsh conditions. Our employees develop customers for life through their daily commitment to expertise, productivity and efficiency. For more information, visit www.IRCO.com.