

Controllo compressore centrifugo serie Xe

Il display a colori ad alta risoluzione e intuitivo del controller serie Xe facilita il reperimento veloce dei dati importanti relativi al compressore. Il controller può pubblicare i dati sulle pagine Web locali e quando rileva un problema può anche inviare una notifica per e-mail. Tra i controlli della serie Xe vi sono utili timer e avvisi che indicano quando sono necessari interventi per ottimizzare la manutenzione del vostro prodotto. I controlli della serie Xe utilizzano i più recenti algoritmi di controllo e la più moderna logica incorporata per offrire il più basso consumo d'energia in ogni situazione, gestendo precisamente la pressione di scarico e potenziando al massimo l'apertura della farfalla. ; Fate clic qui per vedere una dimostrazione del controller Xe-145F

Caratteristiche

Achieving best-in-class efficiency is very important at Ingersoll Rand. Xe-145F Series controls utilise the latest control algorithms to provide the lowest energy consumption in every situation. Built-in control logic ensures system reliability by precisely managing discharge pressure, while maximising throttle range. The controller features useful timers, compressor information and alerts that indicate when maintenance is necessary to help optimise care of your investment.



Standard Control:

- **Constant pressure control** – Dynamically maintains precise discharge pressure throughout the full range of operating capacity (100% to 0%). Constant pressure control is used to minimise process pressure variations with rapid reaction to sudden demand variations.
- **Auto-dual control** – Uses inlet modulation to maintain constant system pressure over the compressor's full turndown range. When the load drops below the turndown range, the controller automatically transitions to load/unload mode. Programmable auto-dual control optimises operating efficiency when process demand varies widely over time.
- **Energy Smart Set Point™ (ESS)** – Adjusts a compressor's pressure set point internally to balance and share load between multiple compressors in the same system. ESS reduces the amount of bypassed air, which saves energy.

Optional Control:

- **Ambient Control software** – Maximises a compressor's operating throttle range, increasing usable turndown and substantially reducing or eliminating wasteful compressed air bypass in changing ambient conditions.
- **Integrated Multi-Machine Control (IMMC)** – Automatically sequences and assigns pressure schedules to multiple compressors to minimise the number of compressors operating at any given time and achieve optimum efficiency.

Componenti E Accessori



Parti di ricambio per
compressore centrifugo



Lubrificante per
compressore centrifugo



About Ingersoll Rand Inc. Ingersoll Rand Inc. (NYSE:IR), driven by an entrepreneurial spirit and ownership mindset, is dedicated to helping make life better for our employees, customers and communities. Customers lean on us for our technology-driven excellence in mission-critical flow creation and industrial solutions across 40+ respected brands where our products and services excel in the most complex and harsh conditions. Our employees develop customers for life through their daily commitment to expertise, productivity and efficiency. For more information, visit www.IRCO.com.