CCN 47598281001 Rev C FCN 14252



COMPRESSOR DATA SHEET

Federal Uniform Test Method for Certain Air Compressors Not Applicable

Rotary Compressor: Fixed Speed

| MODEL DATA - FOR COMPRESSED AIR | | | | | | |
|---------------------------------|---|--------------------------------|-------------------------|--|--|--|
| 1 | Manufacturer: Ingersoll Rand | | | | | |
| | Model Number E185ie-W110 (NA-IP55) | Date: | March 2021 | | | |
| 2 | Air-cooled X Water-cooled | Type: | Screw | | | |
| | Oil Injected X Oil-Free | # of Stages: | 2 | | | |
| 3* | Rated Capacity at Full Load Operating Pressure a, e | 1281 | acfm ^{a, e} | | | |
| 4 | Full Load Operating Pressure ^b | 100 | psig ^b | | | |
| 5 | Maximum Full Flow Operating Pressure ^c 110 | | psig ^c | | | |
| 6 | Drive Motor Nominal Rating 250 | | hp | | | |
| 7 | Drive Motor Nominal Nominal Efficiency | ninal Nominal Efficiency 96.5% | | | | |
| 8 | Fan Motor Nominal Rating (if applicable) 2.4 | | hp | | | |
| 9 | Fan Motor Nominal Nominal Efficiency | 82.5% | percent | | | |
| 10* | Total Package Input Power at Zero Flow ^e | at Zero Flow ^e 49.9 | | | | |
| 11 | otal Package Input Power at Rated Capacity and Full pad Operating Pressure ^d 205.3 | | kW^d | | | |
| 12* | Specific Package Input Power at Rated Capacity and Full Load Operating Pressure ^e | | kW/100 cfm ^e | | | |

^{*} For models that are tested in the CAGI Performance Verification Program, these are the items verified by the third party program administrator.

Consult CAGI website for a list of participants in the third party verification program:

www.cagi.org

NOTES:





- a. Measured at the discharge terminal point of the compressor package in accordance with ISO 1217, Annex C; ACFM is actual cubic feet per minute at inlet conditions.
- b. The operating pressure at which the Capacity (item 3) and Electrical Consumption (item 11) were measured for this data sheet.
- c. Maximum pressure attainable at full flow, usually the unload pressure setting for load/no load control or the maximum pressure attainable before capacity control begins. May require additional power
- d. Total package input power at other than reported operating points will vary with control strategy.
- e. Tolerance is specified in ISO 1217, Annex C, as shown in table below.

NOTE: The terms "power" and "energy" are synonymous for purposes of this document.

| Volume Flow Rate at specified conditions | | Volume Flow Rate ^f | Specific Energy ^g Consumption | No Load / Zero Flow Power ^e |
|--|-----------------------|-------------------------------|--|---|
| m ³ /min | ft ³ / min | % | % | |
| Below 0.5 | Below 17.6 | +/- 7 | +/- 8 | |
| 0.5 to 1.5 | 17.6 to 53 | +/- 6 | +/- 7 | +/- 10% |
| 1.5 to 15 | 53 to 529.7 | +/- 5 | +/- 6 | |
| Above 15 | Above 529.7 | +/- 4 | +/- 5 | |

ROT 030.2

2/19 Rev 3 This form was developed by the Compressed Air and Gas Institute for the use of its members participating in the PVP. CAGI has not independently verified the reported data.